



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/600,035	06/20/2003	Werner Kleine	DT-6528	6367
30377	7590	04/19/2006	EXAMINER	
DAVID TOREN, ESQ. ABELMAN FRAYNE & SCHWAB 666 THIRD AVENUE NEW YORK, NY 10017-5621			GATES, ERIC ANDREW	
			ART UNIT	PAPER NUMBER
			3722	

DATE MAILED: 04/19/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

**Office Action Summary**

Application No.

10/600,035

Applicant(s)

KLEINE ET AL.

Examiner

Eric A. Gates

Art Unit

3722

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

**Period for Reply**

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

**Status**

- 1) ☒ Responsive to communication(s) filed on 19 January 2006.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

**Disposition of Claims**

- 4) ☒ Claim(s) 1-20 is/are pending in the application.
- 4a) Of the above claim(s) 12 is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1-11 and 13-20 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

**Application Papers**

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 19 January 2006 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
- Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
- Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

**Priority under 35 U.S.C. § 119**

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some \* c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

**Attachment(s)**

- 1) ☐ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- 3) ☐ Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)  
Paper No(s)/Mail Date \_\_\_\_\_
- 4) ☐ Interview Summary (PTO-413)  
Paper No(s)/Mail Date. \_\_\_\_\_
- 5) ☐ Notice of Informal Patent Application (PTO-152)
- 6) ☐ Other: \_\_\_\_\_

### **DETAILED ACTION**

1. This office action is in response to Applicant's amendment filed on 19 January 2006.

#### ***Claim Objections***

2. Claim 17 is objected to because of the following informalities:
  - a. In line 6, the word "chuck" should be preceded by the word "the".
  - b. In line 9, the word "width" should be preceded by the word "the".
  - c. In line 10, the word "is" should be deleted.
  - d. In line 12, the word cooperation should be preceded by the word "is".
  - e. In line 12, the word "respective" should be preceded by the word "the".Appropriate correction is required.

#### ***Claim Rejections - 35 USC § 103***

3. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

4. Claims 1-15 and 18-19 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kleine (EP 0 304 002 A1).

Art Unit: 3722

5. Regarding claim 1, Kleine discloses a shank for a rotary and/or percussive tool, comprising at least two, axially spaced, guide regions 11; at least one radially projecting entrain strip 16; and at least one locking groove 18 arranged between the at least two guide regions 11 and axially closed at one end thereof for receiving at least one radially displaceable and axially displaceable, within predetermined limits, locking member 49 of chuck, wherein at least one of the at least two guide regions 11 has a guide dimension (not labeled, see Fig 1), and an axial region (not labeled, see Fig 1) of the at least one locking groove 18 has a cross-sectional width (not labeled, see Fig 2) that includes a radial extent of the entrain strip 16, and a thickness (not labeled, see Fig 2) measure in a direction transverse to the width measurement direction, and wherein the guide dimension is greater than the thickness but smaller than the width.

Kleine does not disclose that the locking groove 18 is axially closed at both ends. Kleine does teach a locking groove 12 (closed groove 12 as shown in figure 1) that is axially closed on both ends for the purpose of providing a stronger retention means for use with a chuck. Therefore it would have been obvious to one having ordinary skill in the art at the time the invention was made to have combined the locking groove 18 of Kleine with the locking groove 12 of Kleine in order to simplify the design and increase the chuck retention strength of locking groove 18.

6. Regarding claim 2, the modified invention of Kleine discloses the axial region of the at least one locking groove 18 and at least one of the guide regions 11 have a substantially same cross-sectional surface within a tolerance range of +/- 10%, based on calculations taken from measurements of Figures 1 and 2.

Art Unit: 3722

7. Regarding claim 3, the modified invention of Kleine discloses that at least one of the opposite ends of the at least one locking groove 18 has one of a spherical and cylindrical axial stop surface 21 engageable by the locking member 49 having, respectively, one of a spherical and cylindrical shape.

8. Regarding claim 4, the modified invention of Kleine discloses a maximum aperture angle (not labeled, see Figure 2) of a bottom surface of the at least one locking groove 18, which is defined by a cross-section of the axial region of the at least one locking groove, amounts to at least 120 degrees, based on measurements of Figure 2.

9. Regarding claim 5, the modified invention of Kleine discloses a second, radially projecting, entrain strip 16 located diametrically opposite the at least one entrain strip, wherein a bottom surface of the at least one locking groove 18, which is located between the at least one and second entrain strips 16, forms a first functional surface (not labeled, see Figure 2) formed of smooth surface sections exhibiting one of a smooth transition and a sharp edge transition, with a transition region being curved in a direction to a tool axis.

10. Regarding claim 6, the modified invention of Kleine discloses that the smooth surface sections are even.

11. Regarding claim 7, the modified invention of Kleine discloses a second locking groove 18 arranged diametrically opposite the at least one locking groove 18, with a bottom surface of the second groove, which is located between the at least one and second entrain strips, forming a second functional surface (not labeled, see Figure 2) located opposite the first functional surface.

Art Unit: 3722

12. Regarding claim 8, the modified invention of Kleine discloses the at least one guide region 11 has a cylindrical outer surface.

13. Regarding claim 9, the modified invention of Kleine discloses a second entrain strip 16, which is arranged diametrically opposite the at least one entrain strip 16, is provided in the axial region of the at least one locking groove 18.

14. Regarding claim 10, the modified invention of Kleine discloses a second locking groove 18 arranged diametrically opposite the at least one locking groove 18 and having a same shape.

15. Regarding claim 11, the modified invention of Kleine discloses a second entrain strip 16 arranged diametrically opposite the at least one entrain strip 16 in the axial region of the locking grooves 18.

16. Regarding claim 13, the modified invention of Kleine discloses further axial regions 12 axially spaced from each other and arranged one of parallel to each other, crosswise to each other, and at an acute angle to each other (see Figure 2).

17. Regarding claim 14, the modified invention of Kleine discloses a third guide region 11 arranged between the axial regions.

18. Regarding claim 15, the modified invention of Kleine discloses a further, segment-shaped guide region (not labeled, see Figure 2) provided between the edge of the locking groove 18 and the peak of the entrain strip 16.

19. Regarding claim 18, the modified invention of Kleine discloses that at the guide dimension of the guide region 11, the width amounts to from the guide region dimension multiplied by 1.2 to the guide dimension multiplied by 1.4, and the thickness amounts to

Art Unit: 3722

from the guide dimension multiplied by 0.6 to the guide dimension multiplied by 0.8, based on calculations taken from measurements of Figures 1 and 2.

20. Regarding claim 19, the modified invention of Kleine discloses wherein the shank comprises a second entrain strip 16 located diametrically opposite the at least one entrain strip 16, the at least one entrain strip and the second entrain strip being located in the axial region of the at least one locking groove 18.

21. Claims 16 and 20 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kleine (EP 0 304 002 A1).

22. Regarding claim 16, Kleine discloses a first tool having a shank having at least two, axially spaced, guide regions 11, at least one radially projecting entrain strip 16, and at least one locking groove 18 arranged between the at least two guide regions and axially closed at one end thereof for receiving at least one radially displaceable and axially displaceable, within predetermined limits, locking member 49 of a chuck, with at least one of the at least two guide regions 11 having a guide dimension (not labeled, see Fig 1), and an axial region (not labeled, see Fig 1) of the locking groove 18 having a cross-sectional width (not labeled, see Fig 2) that includes a radial extent of the entrain strip 16, and a thickness (not labeled, see Fig 2) measured in a direction transverse to the width measurement direction, and with the guide dimension being greater than the thickness (D) but smaller than the width (B).

Kleine does not disclose that the locking groove 18 is axially closed at both ends. Kleine does teach a locking groove 12 (closed groove 12 as shown in figure 1) that is

Art Unit: 3722

axially closed on both ends for the purpose of providing a stronger retention means for use with a chuck. Therefore it would have been obvious to one having ordinary skill in the art at the time the invention was made to have combined the locking groove 18 of Kleine with the locking groove 12 of Kleine in order to simplify the design and increase the chuck retention strength of locking groove 18.

The modified invention Kleine does not distinctly disclose a tool set including a second tool having a similar shank, wherein the axial region of the shank of the first tool has a thickness/width ratio greater than a thickness/width ratio of the axial region of the shank of the second tool. However, it would have been an obvious matter of design choice to make the different portions of the shank of a second tool of whatever relative sizes were desired for the purpose of creating a set of different tools for use with different tooling applications, since such a modification would have involved a mere change in the proportions of components. A change in proportion is generally recognized as being within the level of ordinary skill in the art.

23. Regarding claim 20, the modified invention of Kleine discloses wherein each of the shanks of the first and second tools has a second entrain strip 16 located diametrically opposite the at least one entrain strip 16, the at least one entrain strip and the second entrain strip being located in the axial region of a respective shank 11.

24. Claims 17 is rejected under 35 U.S.C. 103(a) as being unpatentable over Kleine (EP 0 304 002 A1).



Art Unit: 3722

25. Regarding claim 17, Kleine discloses a chuck 40 for receiving a shank of a tool and having at least two, axially spaced, guide regions 11, at least one radially projecting entrain strip 16; and at least one locking groove 18 arranged between the at least two guide regions and axially closed at one end thereof for receiving at least one radially displaceable and axially displaceable, within predetermined limits, locking member 49 of the chuck, with at least one of the at least two guide regions 11 having a guide dimension (not labeled, see Fig 1), and an axial region (not labeled, see Fig 1) of the locking groove 18 has a cross-sectional width (not labeled, see Fig 2) that includes a radial extent of the entrain strip 16 and a thickness (not labeled, see Fig 2) measured in a direction transverse to the width measurement direction, and with the guide dimension being greater than the thickness but smaller than the width, the chuck comprising two axially spaced inner guide surfaces 43 (separated by lead 50) in cooperation with the respective guide regions of the shank (through entrain strip 16); at least one locking member 49 radially displaceable over a distance smaller than a half of the guide dimension of the guide region of the shank; and at least one rotation-transmitting element (vertical peaks of inner diameter 53 as shown in Fig 5) circumferentially offset relative to the locking member 49 and having a radial extent, with respect to a tool axis (not labeled, shown in Fig 4) greater than a half of the guide dimension.

Kleine does not disclose that the locking groove 18 is axially closed at both ends. Kleine does teach a locking groove 12 (closed groove 12 as shown in figure 1) that is axially closed on both ends for the purpose of providing a stronger retention means for use with a chuck. Therefore it would have been obvious to one having ordinary skill in

Art Unit: 3722

the art at the time the invention was made to have combined the locking groove 18 of Kleine with the locking groove 12 of Kleine in order to simplify the design and increase the chuck retention strength of locking groove 18.

### ***Response to Arguments***

26. Applicant's arguments, see page 14, the second to last paragraph, filed 19 January 2006, with respect to the rejection(s) of claim(s) 1-17 under 35 U.S.C. 102(b) have been fully considered and are persuasive. Therefore, the rejection has been withdrawn. However, upon further consideration, a new ground(s) of rejection is made in view of Kleine (EP '002).

27. Applicant's remaining arguments fail to comply with 37 CFR 1.111(b) because they amount to a general allegation that the claims define a patentable invention without specifically pointing out how the language of the claims patentably distinguishes them from the references.

28. For the reasons as set forth above, the rejections are maintained.

### ***Conclusion***

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Eric A. Gates whose telephone number is 571-272-5498. The examiner can normally be reached on Monday-Thursday 7:45-6:15.


Art Unit: 3722

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Boyer Ashley can be reached on 571-272-4502. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).



EAG  
16 April 2006



BOYER D. ASHLEY  
SUPERVISORY PATENT EXAMINER